



PRODUCT INFORMATION

#35391A1

Aircraft Hydraulic Fluid Remover (AHFR) is a mix-blend cleaner base on fatty ester and designed to easily remove hydraulic fluid. AHFR has been tested and approved for AMS – 1526B specifications by SMI Inc, Miami, USA.

Advantages:

- ✓ Non-toxic
- ✓ Non-flammable
- ✓ No phosphates
- ✓ High biodegradability (tested by TNO Delft, Netherlands)
- ✓ Classified as a non-dangerous preparation.
- ✓ Not subject to dangerous goods regulations.
- ✓ Quickly de-emulsifies, resulting in an excellent separation of oil and water

Applications:

AHFR is specially formulated to remove sticky hydraulic oil deposits from aircraft fuselages, wheel and landing gear areas. AHFR also removes various types of oils and greases and hydrocarbon deposits. AHFR is environmentally benign and replaces chlorinated products and solvent based cleaners. AHFR is a ready for use product and may also be used as a spot cleaner on aircraft.

Directions for use:

- Shake before use, spray the product on the surface to be cleaned
- Depending from the thickness of the hydraulic oil layer, let the product work for 1 to max 15 minutes.
- Rinse off with water

It is recommended to re-treat the complete aircraft afterwards with ETS Aircraft Cleaner. This product will create an anti-static layer on the fuselage and reduce the adherence of hydraulic oil deposits in the future.

Package:

20 Ltr, 210 Ltr, 1,000 Ltr.

Shelf life:

4 years

Storage:

- Do not store under 35 ° F / 2° C and not above 122° F / 50° C
- Do not use below 35 ° F / 2° C.

Water Danger Class 0



Certified ISO 9001 by



Accredited by the
Dutch Council for
Certification

Also available: Internal cleaners and solvent-free engine and bearing cleaners, wheel cleaners, etc. for further information please contact ETS International Turkey Ltd.

IN ACCORDANCE WITH THE REACH-ENACTMENT (EG) -Nr. 1907/2006, art.31 appendix II